

Cold Water Electric Belt Drive

CW Premium Series

The stationary version of the CW electric series is designed for wash bays, golf courses and restaurant applications where mobility isn't necessary. The stainless-steel package design ensures longevity even in the toughest environments.



NEMA 5-20P,
20-amp plug



NEMA L15-20P,
20-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-30P,
30-amp plug



US
CSA
CERTIFIED



Belt drive triplex piston General pump with ceramic plungers accepts incoming water up to 175°F



CW-2004-SME1 shown with standard low pressure detergent injector



CW-2004-SME3 shown on optional stainless-steel wall mounting bracket (AW-9501-0000)

Pump

- Belt drive triplex piston General pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- In-line water strainer
- Quick connect low pressure detergent injection
- Bypass system

Motor

- Open drip-proof motor (1000 & 3000-PSI models)
- Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models)
- 4-foot electrical cord with ground fault circuit interrupter (NEMA 5-20P, 20-amp plug on CW-1003-SME1)

Frame

- Stainless-steel base and frame
- Removable panel for pump access
- Easy-to-access cabinet design
- Four rubber isolators

Components

- Dual cogged belt drive system for increased belt life
- Conveniently located on/off switch
- Time delay shutdown will shut unit off automatically when trigger gun is released and timer reaches setting

Units Include:

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x 3/8-inch pressure hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

Warranties



MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-1003-SME1	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	NEMA 5-20P	29.5in.x20.5in.x15in.	222 lb.	172 lb.
CW-2004-SME1	2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	NEMA 6-30P	29.5in.x20.5in.x15in.	272 lb.	214 lb.
CW-2004-SME3	2000	3.9	6.0 HP, 230V, 3Ø, 15.0A	NEMA L15-20P	29.5in.x20.5in.x15in.	262 lb.	204 lb.
CW-3004-SME3	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	NEMA L15-30P	29.5in.x20.5in.x15in.	292 lb.	234 lb.

*208V & 460V motors available as options.

ACCESSORIES & OPTIONS

PART NUMBER	DESCRIPTION	FITS MODELS
AW-9501-0000	Stainless-steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0000	Powder coated steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
CX-0069	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled unit will restart	All models
CX-0076	460V, 3-phase models - For when you have 460V of power available	CW-2004-SME3
CX-0077	460V, 3-phase models - For when you have 460V of power available	CW-3004-SME3
CX-0078	Remote box - Adds control box which may be mounted away from unit to control on/off, N/A on models with auto start/stop	All models
CX-0087	208V, single-phase - For when you have 208V of power available	CW-2004-SME1
CX-0088	208V, 3-phase models - For when you have 208V of power available	CW-2004-SME3
CX-0090	208V, 3-phase models - For when you have 208V of power available	CW-3004-SME3
CX-0096	Hour meter - Displays number of hours unit has been in operation	All models