Legacy Undercarriage Cleaner



Legacy is proud to offer the Undercarriage Cleaner, an ideal way to clean under vehicles and heavy equipment.

- No more crawling under a vehicle
- Simply connect to your hot or cold water pressure washer
- · Easy to handle & maneuver
- Removes road grime, fuel & oil contaminants
- Removes snow sludge & ice
- Provides a clean working environment for technicians
- Stainless steel rotating assembly built to withstand pressures up to 4000 PSI and 250°F
- 5.5" Required Clearance
- 4 Nozzles: (2) 0° #2.0, (2) 25° #2.0





Part No.	Description
8.749-303.0	Undercarriage Cleaner

Cyclone Rotary Surface Cleaner





The "Cyclone" rotary surface cleaner can be used with most hot and cold water washers. It reduces overspray and zebra striping. Great for warehouse floors, sidewalks, pool decks, parking lots, etc.

- 4-8 GPM
- 1000 4000 PSI
- 200°F
- · Polyethylene housing
- · Collapsible handle
- · Pneumatic tires
- 20" diameter surface cleaning
- Up to 8 gpm
- · Weight: 35 lbs

Part No.	Original No.	Description
8.903-608.0	30-587	"Cyclone" Surface Cleaner
8.751-358.0		Replacement Swivel
8.751-886.0		Complete Swivel Rebuild Kit
8.751-361.0		Swivel Rebuild Kit, Swivel Inlet

Whisper Wash Flat Surface Cleaners

Public Facilities

Restaurants

Gondolas

Stadiums

- · Saves labor, fuel & water
- · Eliminates overspray and zebra striping
- Use with conventional pressure washers
- . Use with cold or hot water
- · Balanced spray bar
- · Quick connection
- 2.000 to 4.000 PSI

Driveways

Sidewalks

School Yards

And lots more!!

2500 RPM

Applications:

- · Service Stations
- Pool & Patio Decks
- Warehouse Floors
- Loading Docks
- · Parking Lots
- Marina Docks

The "Maxima 36"

- · Portable Breakaway Handle
- 212°F
- 4-10 GPM
- 2500 RPM
- Dimensions: Cover: 36" Handle: 77
- · Weight 37 lbs



Part No.	Original No.	Description	
8.710-089.0	343636	Maxima 36	
8.701-884.0		Swivel Complete	
8.701-879.0		Repair Kit	

Ground Force

- · Flip and fold handle
- · Choice of 2 or 4 nozzles
- · Rebuildable swivel
- 212°F
- 4-10 GPM
- Dimensions: 24" x 60" x 9"
- Weight 29 lbs

Part No.	Original No.	Description
8.710-076.0	343608	Ground Force
8.701-884.0		Swivel Complete
8.701-879.0		Repair Kit

Whisper Wash Flat Surface Cleaners

- continued

The "Big Guy"

- · Powder coated aluminum housing
- Oversized, self-lubricating twin thrust bearings
- · Choice of 2 or 4 nozzles
- 10" pneumatic tires, 4" caster
- Crafted with durable stainless steel & aircraft aluminum
- 212°F
- 4-10 GPM
- Dimensions: 28" x 44" x 12"
- Weight 48 lbs

Part No.	Original No.	Description
8.710-074.0	343606	Whisper Wash Big Guy 2 Nozzles
8.710-075.0	343607	Whisper Wash Big Guy 4 Nozzles
8.750-604.0	092110	Swivel, Complete Big Guy & Classic
8.701-879.0	092105	Repair Kit, Seal, Big Guy & Classic
8.701-874.0	092101	Spraybar, 4 Nozzle, Big Guy
8.701-876.0	092102	Spraybar, 2 Nozzle, Big Guy

The Classic

- · Portable breakaway handle
- ABS Housing
- 2" nylon brush
- 212°F
- 4-10 GPM
- Dimensions: 19" x 77" x 12"
- · Weight 28 lbs



Part No.	Original No.	Description
8.710-073.0	343605	Whisper Wash Classic
8.750-604.0	092110	Swivel, Complete Big Guy & Classic
8.701-879.0	092105	Repair Kit, Seal, Big Guy & Classic

The Ultra Clean WW

- ABS Housing
- Four 3" casters
- · Powder coated handle
- 185°F
- 3-6 GPM
- 2500 RPM
- Dimensions: 19" x 43" x 9"
- Weight 23 lbs



Part No.	Original No.	Description	
8.710-072.0	343604	Whisper Wash Ultra Clean WW	
8.701-883.0		Swivel Complete, Ultra Clean	
8.701-8882.0		Swivel Repair Kit	

Whisper Wash Flat Surface Cleaners



- · ABS Housing
- 2" nylon brush
- · Powder coated handle
- 185°F
- 3-6 GPM
- Dimensions: 16" x 43" x 9"
- · Weight 19 lbs

The Ultra Clean HC

Part No.	Original No.	Description
8.710-071.0	343603	Whisper Wash Ultra Clean HC
Repair Kits		
Part No.	Original No.	Description
8.701-879.0	092105	Seal Kit; Classic, Big Guy & Ground Force
8.701-882.0	092108	Seal Kit; Ultra Clean
8.701-883.0	092109	Complete Swivel Kit; Ultra Clean
8.750-604.0	092110	Complete Swivel Kit; New Style Classic, Big Guy & Ground Force
8.707-653.0	251119	2.5 x 25° 1/4" nozzle fits All Models

SideWinder Surface Cleaner



Part No.	Original No.	Description
8.739-431.0	343690	SideWinder 105F Fixed Black

Mosmatic Gun Swivel



Mounts to your high pressure gun or lance for an easy turning, low maintenance aun swivel

- 4000 PSI
- 250°F
- 30 RPM

Part No.	Original No.	Description
8.712-467.0	421057	1/4" MPT / 1/4" FPT Gun Swivel
8.712-466.0	421056	3/8" MPT / 3/8" FPT Gun Swivel

Mosmatic MOSMATIC **Surface Cleaners & Duct Cleaner**

Turbo Surface Cleaner

Delivers high-pressure performance with low maintenance for any hot or cold pressure washer. Completely stainless steel design makes this the toughest surface cleaner available in the pressure cleaning market.



seal bushings for long-lasting operation under tuff conditions.

Ideal for Pressure Washer Contractor to clean Walls, Ceilings, Public Facilities, Tile Floors and other hard to reach areas. Uses 1/8" meg 1503 nozzles.

Swiss engineered with high RPM Swivel fea-

tures reinforced self-lubricated stainless steel

ball bearings and dual spring based carbide



4000 PSI

Duct Cleaner

Designed as an accessory for use with high pressure pumps or pressure washers. Cleans Ducts, Chutes, Vents, Restaurant Exhausts, Tanks, etc.

Self rotating and feeding stainless steel triple bearing system for constant easy turning. Nozzle holders are 1/8" NPTF. Nozzles are sold separate.



- 250°F 4000 PSI

• 6.5lbs

Inlet Ports: 3/8" NPTF

12" Surface Cleaner

Designed for effortless cleaning of small areas including walls and angled surfaces.

High RPM swivel with integrated toggle joint and adjustable tension system.

- 250°F
- 4000 PSI
- 9lbs
- 12" SS Cover



Part No.	Original No.	Description	PSI
8.712-284.0	411171A	Turbo Cleaner - 8"	4000
8.712-285.0	411172	Toggle Joint KGK	4000
8.712-280.0	411156	Duct Cleaner TXR-2s, Adjustable	4000
8.712-279.0	411155	Duct Cleaner TXR-2s, Fixed	4000
8.749-911.0		Surface Cleaner - 12"	4000

Mosmatic Roof Cleaner



Industrial quality tool specially designed for efficient, high pressure roof cleaing while keeping the operator in a safe area.

- 21-inch
- 4000 PSI
- 250°F
- 31.9 lbs.
- · Pressure gauge
- · Ball valve
- · Adjustable Wheels (height & width)
- · Safety eye connection for rope or cable
- (2) 1/8" nozzles sold separately



Part No.	Description	
8.749-910.0	Mosmatic Roof Cleaner	

Mosmatic Surface Cleaners with Recovery

- · Stainless Steel Housing with Adjustable Casters
- 250° F / 120° C
- 5.000 PSI / 345 BAR
- 2" Vacuum Hook-Up

Part No.	Description		
8.751-299.0	Surface Cleaner, 21" With Recovery		
8.751-300.0	Surface Cleaner, 21" with Gum Remover and Recovery		
8.751-301.0	Gum Remover Nozzle (For Use with 8.751-300.0)		
Replacement S	wivel and Repair Kits		
8.712-470.0	Complete Swivel, 8.751-299.0		
8.712-483.0	Swivel Repair Kit		

▼ KXRCHER

Electric-Powered, Diesel-Heated Hot Water Heating Module

Add hot water cleaning economically! Portable water heater add-on for existing cold water pressure washers. Quick Connect to cold water washer, supply fuel and power to Euro-Heat for hot water cleaning applications - USE ONLY WHEN NEEDED and keep the convenience of the portable cold water washer.



Part No.	Description
1.575-650.0	5 GPM / 3000 PSI - 120V, 1 ph

Goff's Curtain Walls

Build a Power Wash Cell to meet your needs. Goff's Curtain Walls™ increase useable floor space while controlling overspray, contaminants, climate, and noise levels. Curtain Walls™ glide easily on steel track and dual-wheeled rollerhooks. Made from a combination of 14-oz. heavy-duty, reinforced vinyl and doublepolished 20-mil clear PVC material. Reinforced hems and chain-weighted lower hems add durability. Hook and loop fasteners on side hems attach to adjacent panels. Meet NFPA-701 requirements for flame retardancy. Curtains are also rot and mildew resistant. Standard model has a white vinyl top, clear PVC center, and blue vinyl bottom.










- #2 Brass tooth grommets on 1' centers
- 14 oz. reinforced vinyl white top section
- · All seams double locked stitched
- . Hook & Loop Fasteners allow adjacent panels to be easily attached to one another
- 20 mil. double polished clear window
- All sections joined together using mildew/ rot resistant thread
- 14 oz. reinforced colored vinyl section (your choice of over 12 different colors)
- · Chain weighted lower hem









Part No.	Original No.	Description	PSI	
Single				
9.841-694.0	681133	6' width x 12' high	1500	
8.717-007.0	681083	12' width x 8' high	1500	
8.717-008.0	681084	12' width x 9' high	1500	
8.739-485.0	681082	12' width x 12' high	1500	
8.717-009.0	681086	24' width x 10' high	1500	
8.739-486.0	681087	24' width x 12' high	1500	
Station				
9.841-695.0	681145	4-sided x 12' high	1500	

includes hardware, track & rollers (white top, clear center & blue bottom panel) All 2,3 & 4-sided stations are 12' wide x 24' long (see diagram above)

Other sizes available - call for details

Water Broom 16"





- 4000 PSI
- Fits any 1/4" wand
- Requires (4) 1/4" nozzles and wand

Part No.	Original No.	Description	
8.710-082.0	343615	Water Broom 16"	
0.710-002.0	343013	Water Droom to	1/10

Professional Sandblast Head



- Long-wearing Carbide sand nozzle
- 1/4" FPT water inlet
- 200°F
- 10 GPM
- 3500 PSI
- Sand probe weight 6 oz, length 16"
- · Head weight 13 oz

Nozzle Size	Part No.	Original No.
3.5	8.711-242.0	391631
4.0	8.711-243.0	391632
4.5	8.711-244.0	391633
5.0	8.904-403.0	391634
5.5	8.711-245.0	391635
6.0	8.904-404.0	391636
8.0	8.711-246.0	391637

Part No.	Original No.	Description
8.711-247.0	391640	Sand Probe
8.901-264.0	121041	1/2" ID Polybraid Tubing, 25'

Sandblast Kit - Carbide Nozzle Industrial Grade



A Venturi orifice creates a uniform blast pattern, doubles sand velocity and produces up to 45% more work with 20% less sand.



- 5500 PSI Max Working Pressure
- 10 GPM Max Flow
- 200°F
- 10 lbs.
- · Nozzle tips sold separately

Part No.	Original No.	Description
8.701-485.0	084079	Sand Blast Kit DWSDBTK

Sandblast Nozzles Tips



Replacement tips for Sandblaster Kit (part no. 8.701-485.0 - Original no. 084079)

• Use 1/4" meg 5° spray tip

Part No.	Original No.	Description
8.707-668.0	251159	4.0 x 5° Tip
8.707-685.0	251198	5.0 x 5° Tip
8.707-696.0	251221	5.5 x 5° Tip
8.707-701.0	251237	6.0 x 5° Tip
8.707-709.0	251256	6.5 x 5° Tip

Sandblast Kit - Carbide Nozzle Industrial Grade



A Venturi orifice creates a uniform blast pattern, doubles sand velocity and produces up to 45% more work with 20% less sand.



8.701-617.0

- · Solid carbide blast nozzle
- · Venturi orifice design
- · Volume control sand feed valve
- Up to 3500 PSI
- Up to 750 lbs of sand per hour

Kit contents: Sand head with carbide nozzle, 20" lance, Sand probe, 13-1/2' sand hose, Sand flow regulator valve

Orifice Size	Part No.	Original No.
4.0	8.904-397.0	391554X
4.5	8.904-396.0	391553X
5.0	8.904-398.0	391555X
5.5	8.904-395.0	391550X
6.0	8.904-399.0	391556X
7.0	8.904-400.0	391557X
10.0	8.904-402.0	391560X

Part No.	Original No.	Description
8.701-620.0	086941	Solid Carbide Nozzle only
8.701-617.0	086930	Probe only

Tip-Jet Nozzles for water nozzle replacement or for system volume changes

Orifice Size	Part No.	Original No.
3.0	8.708-016.0	253316
4.0	8.708-019.0	253330
4.5	8.708-023.0	253338
5.0	8.708-027.0	253346
5.5	8.708-031.0	253355
6.0	8.708-035.0	253365
6.5	8.708-039.0	253375
7.0	8.708-042.0	253383
7.5	8.708-046.0	253392
8.0	8.708-050.0	253400
9.0	8.708-054.0	253415
10.0	8.708-058.0	253456

Dual Chemical Systems



- · New deep-ribbed Yellow casing, stays flexible even in cold temperature
- Hose assembly complete with gun and amphenol connectors pre-wired
- · Fully compatible with Power Blaster, Two-Step, Chemex and most other cold water dual chemical systems

Part No.	Original No.	Description
Complete Hose	Assembly	
8.709-044.0	285116	80' R2 Electric (5 wire)
8.709-045.0	285120	100' R2 Electric (5 wire)
Lance Attachme	ent Parts	
8.709-049.0	285136	Female Receiver
8.709-050.0	285137	Male Lance Swivel
8.709-051.0	285138	Retainer Nut
Complete Remo	te Gun Unit	
8.709-046.0	285125	Gun, Electric
Remote Gun/Hos	se Parts	
8.709-048.0	285135	Gun Housing
8.709-053.0	285139	Switch P/B
8.709-054.0	285140	Switch, Chemical
8.709-056.0	285142	Switch Plate
8.903-083.0	285144	O-ring, Nipple (2 req'd)
8.903-084.0	285145	O-ring, Nipple (Bags of 50)
8.709-060.0	285175	Swivel Adapter
8.709-061.0	285177	Cord Grip
8.709-063.0	285181	Oetiker clamp
8.709-064.0	285187	Switch – Push Button Trigger
8.709-065.0	285189	Toggle, DPDT (Trig) On/Off/On

Stainless Steel Sewer Nozzles



- 4100 PSI
- Corrosion Resistant Stainless steel
- · One Forward Orifice
- · Three Rear Orifices

Part No.	Original No.	FPT	Size	
8.710-905.0	373075	1/8"	5.0	
8.710-906.0	373076	1/8"	5.5	
8.710-907.0	373077	1/8"	6.0	
8.710-908.0	373078	1/4"	6.5	
8.710-909.0	373079	1/4"	7.0	
8.710-910.0	373080	1/4"	9.5	

Sewer / Tube Cleaning Nozzles SUTTNER

The reverse jets on the fixed and rotary nozzles pull the hose through the tube or sewer line and blast debris from line or tube walls.



- · Backward ports drive the nozzle forward and flush debris
- · Forward ports blast into pipe and breaks up clogs & debris
- · Physically small for cornering ability
- Corrosion resistant stainless steel construction
- · Orifice size indicated on non-rotating styles
- · Rotating style adds extra agitation and surface cleaning

Part No.	Original No.	Nozzle	Orifice Size	0.D.	Ports
Non-Rotating Se	ewer Nozzle	s			
8.710-875.0	373024	1/8"	4.5	.580"	0-forward, 3 back
8.710-874.0	373023	1/8"	5.5	.580"	1-forward, 3 back
8.710-878.0	373027	1/4"	4.5	.730"	1-forward, 3 back
8.710-876.0	373025	1/4"	5.5	.730"	1-forward, 3 back
8.710-877.0	373026	1/4"	6.0	.730"	1-forward, 4 back
8.710-880.0	373029	1/4"	7.5	.730"	1-forward, 4 back
8.710-879.0	373028	1/4"	8.0	.730"	1-forward, 3 back
8.710-881.0	373032	1/4"	12	.730"	1-forward, 3 back
8.710-885.0	373038	3/8"	4.0	.920"	1-forward, 3 back
8.710-884.0	373037	3/8"	5.5	.920"	1-forward, 3 back
8.710-886.0	373039	3/8"	8.5	.920"	1-forward, 4 back
8.710-883.0	373036	3/8"	12	.920"	1-forward, 4 back
8.710-882.0	373035	3/8"	14	.920"	1-forward, 4 back







0-forward, 3 back ports

1-forward, 3 back ports

1-forward, 4 back ports



- Rotating sewer nozzle
- · Adds extra agitation
- 4000 PSI
- · Back Jet Only

Part No.	Original No.	Rotating Nozzle	Size	Ports
Rotating Sewer	Nozzles			
8.710-899.0	373062	1/8"	5.5	0-forward, 3 back
8.710-898.0	373061	1/4"	5.5	0-forward, 3 back
8.710-900.0	373064	1/4"	8.0	0-forward, 3 back
8.710-887.0	373040	1/4" Duct Clnr*	5.5	0-forward, 2 side

*Duct Cleaner jet to sides instead of reverse







0-forward, 2 side ports

Sewer Hose

SUPER FLEXIBLE SEWER LINE HOSE Hose and couplings have small outside diameter, allowing hose and nozzles to fit through sewer line. Sewer line has

Super Tough poly-ether cover over ultra-flexible nylon tube. (1/8" sewer nozzle and hose will operate through many 1-1/2" lines.)

(Nozzles not included.)

- 160°F
- · Nylon tube, poly-ether cover

Diameter	Length (ft)	Max PSI	End 1	End 2
1/8"	25	4800	1/8" MPT	1/8" MPT
1/8"	50	4800	1/8" MPT	1/8" MPT
1/8"	75	4800	1/8" MPT	1/8" MPT
1/8"	25	4800	1/4" MPT	1/8" MPT
1/8"	50	4800	1/4" MPT	1/8" MPT
1/8"	100	4800	1/4" MPT	1/8" MPT
1/4"	50	2600	1/4" MPT	1/4" MPT
1/4"	100	2600	1/4" MPT	1/4" MPT
1/4"	50	4400	1/4" MPT	1/4" MPT
1/4"	100	4400	1/4" MPT	1/4" MPT
1/4"	150	4400	1/4" MPT	1/4" MPT
1/4"	200	4400	1/4" MPT	1/4" MPT
3/8"	50	4000	3/8" MPT	3/8" MPT
3/8"	100	4000	3/8" MPT	3/8" MPT
3/8"	150	4000	3/8" MPT	3/8" MPT
3/8"	200	4000	3/8" MPT	3/8" MPT
3/8"	250	4000	3/8" MPT	3/8" MPT
3/8"	300	4000	3/8" MPT	3/8" MPT
1/2"	100	4000	1/2" MPT	1/2" MPT
1/2"	150	4000	1/2" MPT	1/2" MPT
1/2"	200	4000	1/2" MPT	1/2" MPT
1/2"	250	4000	1/2" MPT	1/2" MPT
1/2"	300	4000	1/2" MPT	1/2" MPT
1/2"	400	4000	1/2" MPT	1/2" MPT
	1/8" 1/8" 1/8" 1/8" 1/8" 1/4" 1/4" 1/4" 1/4" 1/4" 1/4" 1/4" 1/4	1/8" 25 1/8" 50 1/8" 75 1/8" 25 1/8" 50 1/8" 50 1/8" 100 1/4" 50 1/4" 100 1/4" 50 1/4" 150 1/4" 200 3/8" 50 3/8" 100 3/8" 250 3/8" 250 3/8" 300 1/2" 150 1/2" 250 1/2" 250 1/2" 300	1/8" 25 4800 1/8" 50 4800 1/8" 75 4800 1/8" 25 4800 1/8" 50 4800 1/8" 100 4800 1/4" 50 2600 1/4" 100 2600 1/4" 50 4400 1/4" 100 4400 1/4" 150 4400 1/4" 200 4400 3/8" 50 4000 3/8" 100 4000 3/8" 150 4000 3/8" 200 4000 3/8" 250 4000 1/2" 100 4000 1/2" 150 4000 1/2" 200 4000 1/2" 250 4000 1/2" 250 4000 1/2" 300 4000	1/8" 25 4800 1/8" MPT 1/8" 50 4800 1/8" MPT 1/8" 75 4800 1/8" MPT 1/8" 25 4800 1/4" MPT 1/8" 50 4800 1/4" MPT 1/8" 50 4800 1/4" MPT 1/8" 100 4800 1/4" MPT 1/4" 50 2600 1/4" MPT 1/4" 100 2600 1/4" MPT 1/4" 50 4400 1/4" MPT 1/4" 50 4400 1/4" MPT 1/4" 200 4400 1/4" MPT 1/4" 150 4400 1/4" MPT 1/4" 150 4400 1/4" MPT 1/4" 200 4400 1/4" MPT 1/4" 200 3/8" MPT 3/8" 50 4000 3/8" MPT 3/8" 150 4000 3/8" MPT 3/8" 250 4000 3/8" MPT 3/8" 250 4000 3/8" MPT 1/2" 100 4000 1/2" MPT 1/2" 150 4000 1/2" MPT 1/2" 250 4000 1/2" MPT

Foot Controlled Pressure Valve



Operators of sewer and tube cleaning equipment need both hands free to feed or retract the hose in the sewer line. Foot operated valve allows hands-free control.





- Inlet 3/8" outlet 1/4"
- Brass body Stainless steel valve
- · Steel cover for safety
- Up to 12 GPM
- Up to 5000 PSI

Part No.	Original No.	Description	PSI
8.710-134.0	344200	Sewer Cleaner Foot Valve	3000
8.709-972.0	342024*	Foot Valve w/ ST-2305	5000
8.701-657.0	089006	Repair Kit - Foot valve	
8.701-673.0	089850	Repair Kit ST-2305	
8.711-526.0	4-0193	Kit, 25' Hose, #4.5 Nozzle, F	oot Valve

^{*}Heavy gauge steel construction for durability and stability

ST-36 Pit Boss Sludge Sucker SUTTNER W

Sludge Sucker uses a high pressure water stream (1000-3000 PSI) to suck the sludge off the bottom of pits or tanks and eject it through a 1-1/2" (15' long) hose to a disposal tank.

The base unit attaches to the end of a pressure washer lance with a quick coupler for extension to the bottom of the pit. Uses a 0° tip for suction/power ejection.





- Uses standard 1/4" MPT nozzle
- Easy to change for different plumbing system flows and pressures

Part No.	Original No.	Description
8.711-112.0	376137	ST-35 Pit Boss, 5.5 Nozzle/ 15' Hose
8.711-110.0	376126	(Base unit only)

^{*}w/o hose, nozzle or quick coupler (3/8" inlet port)

Drum Tool Accessories

The Indispensable Tools.











Part No.	Orig. No.	Description
8.712-534.0	449339	Drum Plug Wrench
8.704-689.0	118400	Lid-Off
8.704-691.0	118404	Funnel, 7" x 10"
8.704-692.0	118407	3/4" Faucet
8.704-693.0	118408	2" Faucet
Load Cincher Ti	ie Downs	
8.707-473.0	249938	7/8" x 5-1/2' (Non-Ratchet) "Quick Lock"
8.707-474.0	249939	1" x 15' (Ratchet) "Tight Lock"

Fiberglass "Super Handles"

- · Tough durable lightweight
- · No cracking splintering
- · No kinks dents
- · Safer around electrical hazards
- Easy-Twist cam lock extension
- Super heavy-duty aluminum alloy threads
- Standard 3/4" Acme thread fits: Brooms, brushes, utility tools
- Optional reduction adapter for 3/4" to Acme standard

Part No.	Original No.	Description
Super Handles		
8.709-306.0	306864	48" Length (4 ft)
8.709-307.0	306865	60" Length (5 ft)
8.709-308.0	306866	72" Length (6 ft)
Super-Extension	Handles	
8.709-309.0	306868	4 ft to 8 ft Ext
8.709-310.0	306869	6 ft to 12 ft Ext
8.709-311.0	306870	8 ft to 16 ft Ext
8.700-308.0	075271	Threaded Adapter
		·

Drum / Tank Pump - Crank Type

Chemical-resistant, lightweight pump, ideal for dispensing chemicals, pesticides and oils. **Polypropylene** for most alkalies, dilute acids, pesticides, and most oils & solvents. **Ryton** for extremely aggressive acids, aromatic and aliphatic hydrocarbons.



SPECIFICATION:

- · 11 oz per revolution
- 6 GPM @ 70 RPM
- · Viton seals
- · Polypropylene gasket
- · 2" bung adapter
- Outlet 3/4" barb 2 piece
- 47" suction tube
- · Weight 2.6 lbs

Part No.	Original No.	Description
8.704-700.0	118435	Polypropylene Pump (Standard)
8.704-701.0	118438	Ryton Pump (Deluxe)
8.700-526.0	076975	Replacement Handles

Siphon Pumps

Siphon liquids from higher to lower levels. Simply pump the bellows a few times to prime and start flow. Loosen air lock to stop.



- Drum pump fits 15, 30 & 55 gallon drums
- · Fit 2" bung opening

- Excellent for: Alkaline & acidic chemicals, diesel fuel, & oils
- · Not for use with solvents!

Part No.	Original No.	Description
8.704-698.0	118429	Red Hex Head (Heavy-duty)
8.704-696.0	118423	Red Head (Standard duty)
8.704-694.0	118420	Pail Pump (5 Gallon)

Brushes



Rotating Brush - Natural Bristle (soft) used for painted surfaces. Nylon Bristle (stiff) used for removing scum and grime on fiberglass boats, etc.



 Internal nozzle = size 20)
---	---

Ö	u	۲I	VI	

Part No.	Original No.	Description
Brush Unit Compl	lete	
8.709-312.0	306925	Natural
8.709-314.0	306935	Nylon
Replacement Bru	shes	
8.709-313.0	306927	Natural
8.709-316.0	306937	Nylon

Truck Wash Brush



- · Flag-tipped
- Soft bristle
- ACME thread for Super Handles, or broom handles

Part No.	Original No.	Description
8.709-298.0	306800	2-1/2" Bristle w/Bumper x 10"
8.709-303.0	306818	2-1/2" Bristle x 18"
8.709-304.0	306824	2-1/2" Bristle x 24"
8.709-305.0	306860	60" Flow Thru Lance*

^{*}with Acme Thread & Garden Hose Attachment

Deck Scrub Brush – Over / Under - Unique Heavy-duty Scrub Brush with Multi-Level/Angle.



- Trimmed for cleaning hard-to-reach areas
- 10" molded polypropylene foam block does not warp or absorb water
- Stiff polypropylene bristle for aggressive cleaning
- Excellent chemical resistance
- Use with threaded handle
- Not a Flow Thru

Part No.	Original No.	Description
8.709-302.0	306812	Deck Scrub Brush

Tractor Brush - Soft for gentle cleaning of fine finishes.



Part No.	Original No.	Description
8.709-300.0	306802	Flag Tip Window 10"

Compact Foamer



Generates a high density clinging foam for extended dwell time to increase chemical action



- Stainless steel, aluminum and brass
- 5" long, 1" diameter
- 4 and 6.5 nozzle included
- 1 to 5 GPM
- 195°F
- 2500 PSI

Part No.	Original No.	Description
8.903-998.0	344022V	1/8" F Inlet
0 002-000 O	244022V	1//I" E Inlot

NOTE: Most cleaning chemicals perform best when applied at 120° - 150°F and can be applied as a foam by adding a foaming agent. See your chemical supplier to obtain the correct product.

Foam Cannon

The Ideal Foam Generator Application Accessory meters the foaming chemical for customized foam type and applies the foam to match the application.



- Brass meter valve 3000 PSI max pressure
- High impact glass-filled body
- · 176°F max temperature
- 1/4" FPT lance connect

Part No.	Original No.	Description
8.710-125.0	344030	Foam Cannon/ Injector
8.710-126.0	344032	Foam Cannon/ Injector/Bottle
8.704-222.0	113011	Replacement Turbulator Screen

Air Power Sprayers



- · Pump-up style
- · Heavy-duty plastic sprayers for chemical applications
- Both models have Adj. Nozzle from mist to solid stream
- 2 gallon unit has 2' hose and hand trigger
- · Excellent chemical resistance
- · Locking hand pump handle serves as carrying handle

Part No.	Original No.	Description
8.704-703.0	118842	Thumb Button 3 Pint
8.704-702.0	118835	2 Gallon Sprayer

Foam Jet Kit



Long distance foam applicator. Shoots OVER 20 FEET of dense foam. Suction at 30 feet of height. Varable spray pattern.



- 5000 PSI
- 5.6 GPM
- 14" inlet
- 140° F
- 33' Tube

Part No.	Description
8.750-296.0*	Kit, Foam Jet, 5000 PSI, 5.6 GPM
8.750-429.0	Kit, Repair, Foam Jet Orings/ SS Filter
8.750-430.0	Kit, Repair, Foam Jet, Hose/ Valve/ Filter

Includes tubing and fittings as shown

Lafferty Airless Foam Kit



Includes

- · Machined stainless steel construction
- · Stainless Steel chemical check valve
- · Stainless steel Quick Disconnects
- . 10' chemical tube with strainer
- Color-coded metering tips for up to 21 dilution ratios
- 0° nozzle for increased foam throw distance

Part No.	Water Flow Rate	@2000 PSI	@ 137.9 bar
8.749-908.0	Model 10	4.0 GPM	15.1 LPM
8.749-909.0	Model 20	6.0 GPM	22.7 LPM

Adjustable Foamer with Tank

Control the foam spray angle with the variable fan nozzle



- · Horizontal variable fan nozzle
- GPM: 5.3
- · Foam control adjustment knob
- 140°F

PSI: 2600

Part No.	Description
8.710-124.0	Adjustable Foamer w/ Tank

Thread Lock Products



- Direct replacement for LocTite[®] and Fel-Pro[™] products
- ND[™] anaerobic adhesives are liquid materials that cure to a solid, chemical-resistant plastic state when air is not present
- Excellent lubricant; prevents corrosion and fretting

Part No.	Original No.		Tite® :quiv	Bottle Size	
8.704-644.0	112350	Nut Grade™	242	10 ml	
8.704-645.0	112352	Nut Grade™	242	50 ml	
8.704-646.0	112354	Nut Grade™	242	250 ml	
8.704-648.0	112360	Stud Grade™	271	10 ml	
8.704-649.0	112362	Stud Grade™	271	50 ml	
8.704-650.0	112367	Penetrating Adhesive (Sealant)	290	10 ml	

Nut Grade" and Stud Grade" are trademarks of the Oakland Corp.LocTite® is a registered trademark of the LocTite Corp.

Gloves - Industrial Duty

Industrial Grade Gloves for most industry needs chemical/ heat/ abrasion/laceration protection.



8.704-669.0 Black, 14" PVC Glove lined with cotton for the most demanding chemical handling. Resists alkalines, acids – even works well as a sand-blasting glove.

8.704-668.0 Gray – Split Cowhide work gloves, 2-1/2" gauntlet unlined – Great general purpose work glove.

Part No.	Original No.	Description
8.704-668.0	116105	Gray Roughout
8.704-669.0	116114	Black PVC

Rain Suit - 2 Piece

8.704-666.0

8.704-667.0

116100

116101



Large

Extra Large

Amazing Pocket Reference - 3rd Edition

A ton of information in a 5 oz book!



- Air & gases
- Automotive
- Chemistry
- Electrical
- Physical constants
- Math
- · 3350 conversion factors
- · Plumbing & pipe
- Over 20 other subject areas

Part No.	Original No.	Description
8.712-505.0	449015	Pocket Reference

Shipping Tape & Dispenser

Big 2" x 110 yard rolls of clear. Biaxially-oriented polypropylene for secure packages.





 Heavy-duty tape dispenser with serrated blade

Part No.	Original No.	Description
8.704-707.0	118916	Dispenser Boxed
8.901-249.0	118918	110 Yard Roll

Teflon® Thread Sealing Tape



• Big 1/2" x 520" roll

• Mil - spec #T27730

Part No.	Original No.	Description
8.704-705.0	118905	Thread Sealing Tape

Profit From Power Washing

Geared specifically to determining the profitability, feasibility, and marketability of owning a pressure washing business. It covers the methodology so crucial in both starting and operating a pressure washing service. Topics covered include:



- Marketable Services
- · Equipment Selection
- Equipment Use
- Personal Safety
- · Target Markets
- Customer Relations
- Estimating
- Advertising
- Chemical Selection & Use
- · Important Legal Issues
- Much More...

Part No.	Description
8.750-507.0	Profit From Power Washing