



Hot Water Pressure Washers

HGM Series

HHM & HOM Series



Performance Under Pressure.®

HGM Series

Natural Gas/LP Heater Module

Want to turn up the temperature on your Mi-T-M cold water pressure washer? This natural gas/LP heater module is the perfect add-on to the cold water pressure washer you already have in operation.



Natural gas or LP gas-fired natural draft with aspirating-type burner (10-inch stack on 3506 model, 12-inch on 3508 model)



Electronic ignition with standing pilot automatically lights the burner



On/Off burner switch with adjustable thermostat controls outlet temperature



Fork truck accessible base allows for easy moving



10-inch draft diverter included (21-inch height)



HGM-3506-0E10 shown with JP-2703-0MHB

Additional Features:

- Incoming power 120-volt or 240-volt, single-phase
- Pressure relief valve
- 24-volt control system
- 1/2-inch schedule 80-vertical coil assembly
- Quality gas valve with regulator (max. input 1/2-PSI)
- Inlet and outlet quick connects
- 12-foot x 3/8-inch jumper hose with quick connects included, to hook up to existing pressure washer (12-foot x 1/2-inch jumper hose on HGM-3508-0E10 model)

Frame

- Powder coated steel frame assembly



Diesel/Oil-Heated Heater Module

HHM Series

The HHM Series is an electric-powered, diesel/oil-heated hot water heater module that is the perfect add-on to the cold water pressure washer you already have in operation.

Additional Features:

- On/Off rocker switch
- Quick connect inlets and outlets
- 35-foot power cord with Ground Fault Circuit Interrupter (GFCI)
- 250°F maximum outlet temperature (150°F temperature rise at 4.0-GPM)
- Reedless flow switch
- Horizontal schedule 80 pipe coil heat exchanger
- 12-foot x 3/8-inch high pressure jumper hose (to hook up to existing pressure washer)
- No. 1 or No. 2 fuel oil, diesel or kerosene-fired burner (Bio-fuel not approved at this time)
- Racor fuel/water separator
- Wrinkle-finish powder coated steel frame assembly
- Stainless-steel coil wrap



HHM-3506-0E10

Adjustable thermostat controls outlet temperature



10-gallon capacity polyethylene fuel tank



Diesel/Oil-Heated Heater Module

HOM Series

Additional Features:

- Fuel/water separator
- 1/2-inch schedule 80 vertical coil assembly
- On/Off burner switch with adjustable thermostat controls outlet temperature
- Incoming power 120V single-phase
- Inlet and outlet quick connects
- 10-inch draft diverter included (21-inch height)
- 12-foot x 3/8-inch jumper hose with quick connects, to hook up to existing pressure washer

Frame

- Wrinkle-finish powder coated steel frame assembly
- Fork truck accessible base allows for easy moving



HOM-3506-0E10

On/Off switch with adjustable thermostat



No. 1 or No.2 fuel oil, diesel or kerosene fired burner. (Bio fuel not approved at this time)



Mi-T-M offers a full line of products including; cold and hot water pressure washers, air compressors, portable generators, air compressor/generator combination, air compressor/generator/welder combination, wet/dry vacuums, jobsite boxes, portable heaters, and water treatment systems.

HGM, HHM & HOM Series

Model Number	Max. PSI	Max. GPM	Natural Gas BTU	LP Gas BTU	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HGM-3506-0E10	3500	6.0	338,000 per hr.	326,500 per hr.	24.25in.x26.25in.x49.75in.	466 lb.	346 lb.
HGM-3508-0E10	3500	8.0	650,000 per hr.	619,500 per hr.	34.5in.x34.75in.x54.5in.	767 lb.	707 lb.

OPTIONS

Part Number	Description	Fits Models
HX-0105	Liquid propane (vapor only) - Converts natural gas heater module to operate on liquid propane	HGM-3506-0E10
HX-0116	Stainless-steel coil wrap - Changes powder coated coil wrap to a stainless-steel coil wrap	HGM-3506-0E10
HX-0129	460V incoming power - For when you have 460V of power available	All models
HX-0177	575V incoming power - For when you have 575V of power available	All models
HX-0180	Liquid propane (vapor only) - Converts natural gas heater module to operate on liquid propane	HGM-3508-0E10
HX-0186	Modulating thermostat - Regulating gas valve prevents drastic temperature swings by regulating gas flow at operating temperatures	HGM-3508-0E10
HX-0188	Stainless-steel coil wrap - Changes powder coated coil wrap to a stainless-steel coil wrap	HGM-3508-0E10
HX-0215	230V incoming power - For when you have 230V of power available	All models

Model Number	Max. PSI	Max. GPM	Electrical Voltage/Phase/Amp	Burner Fuel Consumption	BTU Per Hour - Diesel	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HOM-3506-0E10	3500	6.0	115V, 1Ø, 3.2A	2.76 gph	386,400	24.25in.x26.25in.x49.75in.	450 lb.	330 lb.

OPTION

Part Number	Description	Fits Model
HX-0116	Stainless-steel coil wrap - Changes powder coated coil wrap to a stainless-steel coil wrap	HOM-3506-0E10

Model Number	Max. PSI	Max. GPM	Electrical Voltage/Phase/Amp	Burner Fuel Consumption	BTU Per Hour - Diesel	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHM-3506-0E10	3500	6.0	115V, 1Ø, 3.2A	2.76 gph	386,400	56.5in.x30in.x41.5in.	543 lb.	423 lb.

OPTIONS

Part Number	Description	Fits Model
HX-0163	13-inch mag tires - Upgrade to mag tires from white rim tires	HHM-3506-0E10
HX-0171	Skid feet - Stationary applications	HHM-3506-0E10

ACCESSORIES

Part Number	Description	Fits Model
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	HHM-3506-0E10
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	HHM-3506-0E10



Mi-T-M Corporation
 8650 Enterprise Drive
 Peosta, IA 52068
 800-553-9053
 563-556-1235 fax
 corp@mitm.com
 www.mitm.com

Distributed by: